Technical Data

CIKOjoint Primer

Multi-Purpose Primer for joint sealants

Description

CIKOjoint Primer is a solvent based two component epoxy prier recommended for porous concrete and masonry substrates. It has excellent adhesion to concrete and other cementitious substrates.

Properties

- Two component epoxy based system
- Provides excellent adhesion to various types of substrates
- Provides extremely good bonding to sealants
- Exhibits very good sealing properties

Physical properties

	Liquid two)
Form	components system	۱
	part A and B	
Colour	Clear to pale brownish	
Mixing ratio	Pre-Weighed packs	
Solids %	Min. 70	
Finish	Clear gloss	
Flash Point	Above 70 ⁰ C	
Hard dry	24 hours	
Surface dry	Within 2 hours	

Coverage

CIKOjoint Primer will provide coverage of 5.0m² per litre @ 100 microns dry film thickness or 30 linear meter per litre for 20 x 20 joint.

Application method

Apply CIKOjoint Primer by brush, roller or trowel over clean, dry substrate.

Packaging

CIKOjoint Primer is available in 1.0 litre kit



Shelf life

CIKOjoint Primer has a shelf life of 12 months if stored in accordance with CIKO instructions.

Storage

CIKOjoint Primer should be stored under enclosed shaded area at temperatures between $5 - 35^{\circ}$ C.

Precautions

CIKOjoint Primer should not be applied at temperatures below 10 °C.

Health & safety

CIKOjoint Primer should not come in contact with eyes or be swallowed. Ensure adequate ventilation and avoid inhalation of vapours. Applicator should wear appropriate clothes, gloves and goggles. Use of barrier cream is recommended to provide additional skin protection. If comes in contact with eyes, flush with plenty of fresh water and seek medical advice. Refer Material Safety Data Sheet for further details.

Technical Support For any technical support, do not hesitate to contact CIKO team at any time as CIKO offers on and off site services to end users, specifier and contractors.

More from CIKO Middle East

A wide range of construction chemical products are manufactured by CIKO Middle East which includes:

- Concrete admixtures and additives \geq
- \geq Waterproofing and damp proof coatings
- \geq Surface treatments
- \triangleright Flooring and toppings
- \triangleright Grouts and anchors
- \geq Tile adhesives and grout
- \triangleright Concrete repair materials
- Adhesives and bonding agent \geq
- \triangleright Protective coating
- \triangleright Joint Sealants and Moulding compounds
- \triangleright Ancillaries

TDS/JS18 Rev.:2 Issue:C

Note: The information presented herein based on the best of our knowledge and expertise for which every effort is made to ensure its reliability. Although all the products are subjected to rigid quality tests and are guaranteed against defective materials and manufacture,

no specific guarantee can be extended because results depend not only on guality but also on other factors beyond our control 1



P.O.Box : 295, Doha, Qatar ۲.: (+974) 4411 4787 , الدوحــة - قطر T.: (+974) 4411 4787 / 4411 4790 / 4411 4794 E-mail: enquiries@cikome.com فاكس : ۴۹۷۴ ٤٤١١