

CIKOpriimer AC

Acrylic primer undercoat

Description

CIKOpriimer AC is an acrylic polymer emulsion based primer undercoat suitable for interior and exterior above grade vertical masonry surfaces.

CIKOpriimer AC stabilizing characteristics reinforces the performance of exterior high performance top coats.

Properties

- Alkali and efflorescence resistance
- Excellent penetration to substrates
- Quick drying
- Excellent adhesion

Application area

CIKOpriimer AC is recommended for use on new vertical precast and poured concrete surfaces, concrete block, stucco, brick and tilt up masonry structures.

Physical properties

Form	Liquid
Colour	White
Specific gravity	1.02±0.005 @ 25° C
Drying time at 25°C	To touch 30 minutes
Toxicity	Non-toxic
Chloride content	Nil to BS 5075
Flammability	No tendency to flash

Coverage

CIKOpriimer AC will provide coverage of approx. 0.1 litre/m² depending on the surface condition.

Application instructions

Surface preparation

Clean the surface to make it free from dust, oil, loosely adhered particles, paint stains, efflorescence and other contaminations. The surface should be abraded or sand blasted to provide a rough surface before application of primer. Repair cracks, voids and other masonry imperfections with CIKOfill AC.

Application

Always stir well before use. Do not apply material if material, substrate and ambient temp is below 5° and or above 43° C

Apply by brush roller or spray.

On surfaces with regular absorption, the product is applied in one coat. On surfaces with high absorption the product is applied in two coats.

Cleaning

Clean the equipment by washing with warm soapy water and rinse thoroughly.

Packaging

CIKOpriimer AC is available in 5 litre cans, 20 litre pails and 210 litre drums.

Shelf Life

CIKOpriimer AC has a shelf life of 12 months in unopened packs and if stored in accordance with manufacturer instructions.

Storage

CIKOpriimer AC should be stored under enclosed shaded area at temperatures between 5 – 35° C.

Precautions

- CIKOpriimer AC should not be used in temperature below 5° C and above 43° C.
- Adjacent surfaces that are not intended for paint finishing must be protected, respectively covered with foil.

Health & safety

CIKOPrimer AC should not come in contact with eyes or be swallowed. Ensure adequate ventilation and avoid inhalation of vapours. Applicator should wear appropriate clothes, gloves and goggles. Use of barrier cream is recommended to provide additional skin protection. If comes in contact with eyes, flush with plenty of fresh water and seek medical advice.

Refer Material Safety Data Sheet for further details.

Technical Support

For further technical support, do not hesitate to contact CIKO team at any time as CIKO offers on and off site services to end users, specifier and contractors.

More from CIKO Middle East

A wide range of construction chemical products are manufactured by CIKO Middle East which includes:

- *Concrete admixtures and additives*
- *Waterproofing and damp proof coatings*
- *Surface treatments*
- *Flooring and toppings*
- *Grouts and anchors*
- *Tile adhesives and grout*
- *Concrete repair materials*
- *Adhesives and bonding agent*
- *Protective coating*
- *Joint Sealants and Moulding compounds*
- *Ancillaries*

TDS/ST18 Rev.1: Issue:C

Disclaimer: The information presented herein based on the best of our knowledge and expertise for which every effort is made to ensure its reliability. Although all the products are subjected to rigid quality tests and are guaranteed against defective materials and manufacture, no specific guarantee can be extended because results depend not only on quality but also on other factors beyond our control



ص. ب رقم : ٢٩٥ ، الدوحة - قطر
ت : (+974) 4411 4787 / 4411 4790 / 4411 4794
فاكس : +٩٧٤ ٤٤١١ ٤٧٩٢
P.O.Box : 295, Doha, Qatar
T: (+974) 4411 4787 / 4411 4790 / 4411 4794
F: (+974) 44114792
E-mail: enquiries@cikome.com